



LTseries LT206 LT206T

Two-way Loudspeaker System

LT206 is a 6.5", coaxial, two-way, all-weather speaker, with waterproof, dustproof, windproof, anti-uv aging, specially designed dustproof and waterproof cover for input and output, has a pressing device, multi-layer different functional grille. The cabinet meets the IP56 standard. The exposed metal parts are made of stainless steel or aluminum, and the mounting bracket is sprayed with low-carbon steel, which can meet all-weather use (the version suitable for the marine environment can be customized, and the mounting bracket is upgraded to 316 stainless steel). Unit configuration: 1x6.5" ferrite mid-bass and 1x 0.8" exit throat 25mm HF driver coaxial unit, the cabinet is made of polymer compound injection molding. LT206T is equipped with transformer and band switch based on LT206 to achieve a variety of different output powers including constant resistance.

FEATURES

- Pass IP56 testing, meet all-weather use
- The cabinet is made of polymer compound injection molding
- Coaxial point sound source
- Customized unit, better bass performance
- Applications: outdoor restaurants, bars, parks, near-filed sound reinforcement of scenic areas, houseboats and seashores (customized)

产品特点



- 产品通过IP56测试，满足全天候使用
- 箱体采用高分子化合物射出成型
- 同轴点声源
- 特制单元，有较好的低音表现

适用范围

- 户外餐厅、酒吧
- 主题公园、景区近场扩声
- 游艇、海边户外近场扩声（需定制）

LT206是一款6.5"同轴两分音、全天候音箱，具有防水、防尘、防风、抗紫外线老化、输入输出用专门设计的防尘防水盖板，并有迫紧装置，多层不同功能面网。产品满足IP56标准，外露金属件采用不锈钢或铝质喷涂，安装支架为低碳钢喷涂，满足全天候使用(可以定制适应海洋环境的版本，安装支架升级为316不锈钢)，单元配置：1只6.5"铁氧体中低音与1只0.8"喉口25芯高音驱动器组成的同轴单元，箱体采用高分子化合物射出成型。LT206T是在LT206的基础上配置音频变压器及波段开关，实现多种不同输出功率包括定阻。

CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

INPUT VOLTAGE

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

LT206

--
100Hz-18kHz
1×6.5" (165mm)/1.4" voice coil LF
1×0.8" (20mm)/1" voice coil HF
--
100W RMS,400W peak
93dB 1watt/1 metre
113dB continuous,119dB peak
8 ohms nominal
100°×100°
2.8kHz passive
covered barrier strip terminals
313mm×313mm×278mm
6 kg/pc
7.5 kg/pc

LT206T

--
100Hz-18kHz
1×6.5"(165mm)/1.4" voice coil LF
1×0.8"(20mm)/1"voice coil HF
100V
25W/50W/100W/OFF/8Ω
93dB 1watt/1 metre
113dB continuous,119dB peak
8 ohms nominal
100°×100°
2.8kHz passive
covered barrier strip terminals
313mm×313mm×278mm
7 kg/pc
8.5 kg/pc